



CITY OF MONTE SERENO
18041 Saratoga-Los Gatos Road
Monte Sereno, CA 95030
Phone (408) 354-7635 Fax (408) 395-7653
www.cityofmontesereno.org

VOC COMPLIANCE CERTIFICATION

| Adhesive (None) | Manufacturer | CALgREEN Limit ¹ | Actual VOCs |
|-----------------|--------------|-----------------------------|-------------|
| | | | |
| | | | |
| | | | |
| | | | |

| Sealant (None) | Manufacturer | CALgREEN Limit ¹ | Actual VOCs |
|----------------|--------------|-----------------------------|-------------|
| | | | |
| | | | |
| | | | |
| | | | |

| Architectural Coatings (None) | Manufacturer | CALgREEN Limit ¹ | Actual VOCs |
|-------------------------------|--------------|-----------------------------|-------------|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

FORMALDEHYDE COMPLAINT CERTIFICATION

| Product (None) | Manufacturer | Current Limit | Actual |
|---------------------------------|--------------|---------------|--------|
| Hardwood plywood veneer core | | 0.05 | |
| Hardwood plywood composite core | | 0.08 | |
| Particleboard | | 0.09 | |
| Medium density fiberboard | | 0.11 | |
| Thin medium density fiberboard | | 0.21 | |

All carpet installed in the building interior meets the testing and product requirements of the following (check one)

- Carpet and Rug Institute's Green Label
- California Department of Public Health Standard Practice for the testing of VOCs
- NSF/ANSI 140 at the Gold Level
- Scientific Certifications Systems Indoor Advantage™ Gold
- No carpet installed on this project

I certify that the information provided on this form is accurate and that the materials used on this project comply with Section 4.504 (Residential) or 5.504 (Non-Residential) of the 2010 California Green Building Standards Code.

Print Name _____ Signature _____ Date _____

¹See other side of page for VOC limits

TABLE 4.504.3
VOC CONTENT LIMITS FOR ARCHITECTURAL COATINGS^{2,3}
Grams of VOC per Liter of Coating,
Less Water and Less Exempt Compounds

| COATING CATEGORY | EFFECTIVE 1/1/2010 | EFFECTIVE 1/1/2012 |
|---|-----------------------|-----------------------|
| Flat coatings | 50 | |
| Nonflat coatings | 100 | |
| Nonflat-high gloss coatings | 150 | |
| Specialty Coatings | | |
| Aluminum roof coatings | 400 | |
| Basement specialty coatings | 400 | |
| Bituminous roof coatings | 50 | |
| Bituminous roof primers | 350 | |
| Bond breakers | 350 | |
| Concrete curing compounds | 350 | |
| Concrete/masonry sealers | 100 | |
| Driveway sealers | 50 | |
| Dry fog coatings | 150 | |
| Faux finishing coatings | 350 | |
| Fire resistive coatings | 350 | |
| Floor coatings | 100 | |
| Form-release compounds | 250 | |
| Graphic arts coatings (sign paints) | 500 | |
| High temperature coatings | 420 | |
| Industrial maintenance coatings | 250 | |
| Low solids coatings ¹ | 120 | |
| Magnesite cement coatings | 450 | |
| Mastic texture coatings | 100 | |
| Metallic pigmented coatings | 500 | |
| Multicolor coatings | 250 | |
| Pretreatment wash primers | 420 | |
| Primers, sealers, and undercoaters | 100 | |
| Reactive penetrating sealers | 350 | |
| Recycled coatings | 250 | |
| Roof coatings | 50 | |
| Rust preventative coatings | 400 | 250 |
| Shellacs | | |
| Clear | 730 | |
| Opaque | 550 | |
| Specialty primers, sealers and undercoaters | 350 | 100 |
| Stains | 250 | |
| Stone consolidants | 450 | |
| Swimming pool coatings | 340 | |
| Traffic marking coatings | 100 | |
| Tub and tile refinish coatings | 420 | |
| Waterproofing membranes | 250 | |
| Wood coatings | 275 | |
| Wood preservatives | 350 | |
| Zinc-rich primers | 340 | |

1. Grams of VOC per liter of coating, including water and including exempt compounds.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the table.
3. Values in this table are derived from those specified by the California Air Resources Board, Architectural Coatings Suggested Control Measure, February 1, 2008. More information is available from the Air Resources Board.

TABLE 4.504.1
ADHESIVE VOC LIMIT^{1,2}
Less Water and Less Exempt Compounds in Grams per Liter

| ARCHITECTURAL APPLICATIONS | CURRENT VOC LIMIT |
|---|-------------------|
| Indoor carpet adhesives | 50 |
| Carpet pad adhesives | 50 |
| Outdoor carpet adhesives | 150 |
| Wood flooring adhesive | 100 |
| Rubber floor adhesives | 60 |
| Subfloor adhesives | 50 |
| Ceramic tile adhesives | 65 |
| VCT and asphalt tile adhesives | 50 |
| Drywall and panel adhesives | 50 |
| Cove base adhesives | 50 |
| Multipurpose construction adhesives | 70 |
| Structural glazing adhesives | 100 |
| Single-ply roof membrane adhesives | 250 |
| Other adhesives not specifically listed | 50 |
| SPECIALTY APPLICATIONS | |
| PVC welding | 510 |
| CPVC welding | 490 |
| ABS welding | 325 |
| Plastic cement welding | 250 |
| Adhesive primer for plastic | 550 |
| Contact adhesive | 80 |
| Special purpose contact adhesive | 250 |
| Structural wood member adhesive | 140 |
| Top and trim adhesive | 250 |
| SUBSTRATE SPECIFIC APPLICATIONS | |
| Metal to metal | 30 |
| Plastic foams | 50 |
| Porous material (except wood) | 50 |
| Wood | 30 |
| Fiberglass | 80 |

1. If an adhesive is used to bond dissimilar substrates together, the adhesive with the highest VOC content shall be allowed.
2. For additional information regarding methods to measure the VOC content specified in this table, see South Coast Air Quality Management District Rule 1168.

TABLE 4.504.2
SEALANT VOC LIMIT
Less Water and Less Exempt Compounds in Grams per Liter

| SEALANTS | CURRENT VOC LIMIT |
|--------------------------|-------------------|
| Architectural | 250 |
| Marine deck | 760 |
| Nonmembrane roof | 300 |
| Roadway | 250 |
| Single-ply roof membrane | 450 |
| Other | 420 |
| SEALANT PRIMERS | |
| Architectural | |
| Nonporous | 250 |
| Porous | 775 |
| Modified bituminous | 500 |
| Marine deck | 760 |
| Other | 750 |